

**19256B****Lace-up Hoisting Grip for 7/8 in coaxial cable, elliptical waveguide 77, and HELIAX® FiberFeed® Hybrid cable**

Dimensions

Nominal Size	7/8 in
Grip Length, minimum	431.80 mm 17.00 in
Leader Length, minimum	330.20 mm 13.00 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

General Specifications

Tool Type	Hoisting grip
Hoisting Grip Type	Lace-up hoisting grip
Attachment Spacing Intervals	61 m 200 ft
Material Type	Stainless steel
Ordering Note	CommScope® standard product in the United States and Canada
Package Quantity	1
Support Clamp	Not included

Mechanical Specifications

Pull Load Capacity	500 lb
--------------------	--------

Packed Dimensions

Height	3.8 cm 1.5 in
Length	22.2 cm 8.7 in
Width	21.8 cm 8.6 in
Shipping Weight	0.22 kg 0.49 lb

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
China RoHS SJ/T 11364-2006	Below Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

