



# 800-900 MHz DIRECTIONAL ANTENNAS

800-900 MHz DIRECTIONAL ANTENNAS

MODELS YG10-80669 (806-869 MHz.)  
YG10-82496 (824-896 MHz.)  
YG10-89060 (896-960 MHz.)

Absolute reliability in harsh environments is achieved with this Yagi design.

Featuring 10 dB forward gain and 20 dB front-to-back ratio.

All aluminum welded and O-ring construction seals out moisture and prevents intermodulation.

Black polyester powder paint coating is highly resistant to chemicals, abrasives, and ice build-up.

Maximum Power	500 watts continuous
Polarization	Vertical
Vertical Beamwidth	40 degrees
Horizontal Beamwidth	55 degrees
Lightning Protection	Direct ground
Standard Termination	Captive type N Female
Mounting Clamps	Stainless steel U-bolts
Wind Survival	160 mph (258 kph)
Dimensions (h x l)	6 x 30 in. (15 x 76 cm.)
Weight	2.5 lbs. (1.1 kg.)

NEW

MODELS YU10-80669 (806-869 MHz.)  
YU10-82496 (824-896 MHz.)  
YU10-89060 (896-960 MHz.)

Economical reliability is achieved with this rugged Yagi design.

Featuring 10 dB forward gain and 20 dB front-to-back ratio.

All aluminum welded and sealed electrical components prevents intermodulation and corrosion.

Black polyester powder paint coating is highly resistant to chemicals, abrasives, and ice build-up.

Maximum Power	500 watts continuous
Polarization	Vertical
Vertical Beamwidth	40 degrees
Horizontal Beamwidth	55 degrees
Lightning Protection	Direct ground
Standard Termination	Captive type N Female
Mounting Clamps	Stainless steel U-bolts
Wind Survival	160 mph (258 kph)
Dimensions (h x l)	6 x 30 in. (15 x 76 cm.)
Weight	2.5 lbs. (1.1 kg.)

NEW