



Model: **TX160N-**(xxx)

Connector Suffix	Radio Models												
M01 	HYT TC-500/ 508/ 518/ 580/ 600/ 610/ 700 PD506, Motorola GP300/ SP-50/ P1225/ PRO3150/ MAG ONE/ EP150/350/ EP450/ DEP450/DTR620 /RVA50/VLR150												
Speaker Specification:	<table> <tr> <td>Type:</td><td>Type: Transducer moving coil dynamic speaker</td></tr> <tr> <td>Impedance:</td><td>Impedance: 100 (32+68) $\Omega \pm 15\%$ @ 1 KHz</td></tr> <tr> <td>Sensitivity:</td><td>Sensitivity: 103 ± 3 dB @ 1 KHz</td></tr> <tr> <td>Frequency respond:</td><td>Frequency respond: 100 - 4.5 KHz</td></tr> <tr> <td>Rated input power:</td><td>Rated input power: 1 mW</td></tr> <tr> <td>Maximum input:</td><td>Maximum input: 10 mW</td></tr> </table>	Type:	Type: Transducer moving coil dynamic speaker	Impedance:	Impedance: 100 (32+68) $\Omega \pm 15\%$ @ 1 KHz	Sensitivity:	Sensitivity: 103 ± 3 dB @ 1 KHz	Frequency respond:	Frequency respond: 100 - 4.5 KHz	Rated input power:	Rated input power: 1 mW	Maximum input:	Maximum input: 10 mW
Type:	Type: Transducer moving coil dynamic speaker												
Impedance:	Impedance: 100 (32+68) $\Omega \pm 15\%$ @ 1 KHz												
Sensitivity:	Sensitivity: 103 ± 3 dB @ 1 KHz												
Frequency respond:	Frequency respond: 100 - 4.5 KHz												
Rated input power:	Rated input power: 1 mW												
Maximum input:	Maximum input: 10 mW												
Microphone Specification:	<table> <tr> <td>Sensitivity range:</td><td>44 ± 3 dB (0dB=1v/Pa, 1kHz)</td></tr> <tr> <td>Impedance max:</td><td>2.2 k$\Omega \pm 10\%$ @ 1 kHz</td></tr> <tr> <td>Frequency:</td><td>50 Hz - 10 kHz</td></tr> <tr> <td>Current consumption max:</td><td>500 μA RL=2.2 kΩ Vs=3.0 V(DC)</td></tr> <tr> <td>Operation voltage range:</td><td>1.0 - 10 V(DC)</td></tr> <tr> <td>Max sound pressure level:</td><td>110 dB = 1 kHz</td></tr> </table>	Sensitivity range:	44 ± 3 dB (0dB=1v/Pa, 1kHz)	Impedance max:	2.2 k $\Omega \pm 10\%$ @ 1 kHz	Frequency:	50 Hz - 10 kHz	Current consumption max:	500 μ A RL=2.2 k Ω Vs=3.0 V(DC)	Operation voltage range:	1.0 - 10 V(DC)	Max sound pressure level:	110 dB = 1 kHz
Sensitivity range:	44 ± 3 dB (0dB=1v/Pa, 1kHz)												
Impedance max:	2.2 k $\Omega \pm 10\%$ @ 1 kHz												
Frequency:	50 Hz - 10 kHz												
Current consumption max:	500 μ A RL=2.2 k Ω Vs=3.0 V(DC)												
Operation voltage range:	1.0 - 10 V(DC)												
Max sound pressure level:	110 dB = 1 kHz												