

Butterfly Hanger for 2-1/4 in coaxial cable and elliptical waveguide 37



Product Classification

Product Type Hanger kit

Dimensions

Nominal Size	2-1/4 in
Compatible Diameter, maximum	59.944 mm 2.360 in
Compatible Diameter, minimum	58.166 mm 2.290 in
Height	82.00 mm 3.23 in
Length	110.00 mm 4.33 in
Width	38.10 mm 1.50 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

Environmental Specifications

Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F)

General Specifications

Hanger Type	Standard butterfly hanger
Cables per Hanger	1
Color	Silver
Material Type	Stainless steel
Ordering Note	CommScope® non-standard product
Package Quantity	10

Mechanical Specifications

Corrosion Resistance, minimum with no degradation	=500 hours in salt spray chamber
Mounting	3/8 in (M10) drilled cable ladder

Vibration Survival

=4 hours at resonant frequency

Environmental Strength Capability

Double cable weight

Packed Dimensions

Height

33.0 cm | 13.0 in

Length

6.0 cm | 2.4 in

Shipping Weight

0.74 kg | 1.64 lb

Width

22.0 cm | 8.7 in

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

ISO 9001:2015

China RoHS SJ/T 11364-2014

Classification

Compliant

Designed, manufactured and/or distributed under this quality management system

Below Maximum Concentration Value (MCV)

