



SHK-12-2-P

Single Hanger Kit for 1/2 in coaxial cable, double stack; includes hardware and angle adapter

Dimensions

| | |
|------------------------------|----------------------|
| Nominal Size | 1/2 in |
| Compatible Diameter, maximum | 16.256 mm 0.640 in |
| Compatible Diameter, minimum | 15.240 mm 0.600 in |
| Height | 52.00 mm 2.05 in |
| Length | 46.29 mm 1.82 in |
| Width | 25.82 mm 1.02 in |

Electrical Specifications

| | |
|--------------------|--------|
| DTF Effect | 0.1 dB |
| Return Loss Effect | 0.1 dB |

General Specifications

| | |
|----------------------|--|
| Hanger Type | Composite clamp |
| Brand | ValuSite™ |
| Cables per Hanger | 2 |
| Color | Black |
| Includes | Angle adapter Hardware |
| Material Type | Engineered plastic Stainless steel |
| Maximum Stack Height | 2 |
| Ordering Note | CommScope® standard product in Europe, the Middle East, and Africa CommScope® standard product in Mexico, Central America, and South America |
| Package Quantity | 1 |

Mechanical Specifications

| | |
|---|--|
| Corrosion Resistance, minimum with no degradation | =500 hours in salt spray chamber |
| Mounting | M8 hardware |
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| UV Resistance, minimum with no degradation | =100 hours exposure in accelerated UV life chamber |
| Vibration Survival | =4 hours at resonant frequency |
| Environmental Strength Capability | Double cable weight |

Packed Dimensions

| | |
|--------|-------------------|
| Height | 30.4 cm 12.0 in |
|--------|-------------------|

Product Specifications



SHK-12-2-P

| | |
|-----------------|-------------------|
| Length | 2.5 cm 1.0 in |
| Shipping Weight | 0.45 kg 1.00 lb |
| Width | 27.9 cm 11.0 in |