



SSH-78

SnapStak® Hanger for 7/8 in coaxial cable

Dimensions

Nominal Size	7/8 in
Compatible Diameter, maximum	30.988 mm 1.220 in
Compatible Diameter, minimum	26.670 mm 1.050 in
Height	41.00 mm 1.61 in
Length	64.00 mm 2.52 in
Width	40.00 mm 1.57 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

General Specifications

Hanger Type	Snap-in hanger
Cables per Hanger	1
Color	Silver
Material Type	Stainless steel
Maximum Stack Height	3
Ordering Note	CommScope® standard product in Asia Pacific CommScope® standard product in Mexico, Central America, and South America CommScope® standard product in the United States and Canada
Package Quantity	10

Mechanical Specifications

Corrosion Resistance, minimum with no degradation	=500 hours in salt spray chamber
Mounting	3/4 in drilled cable ladder
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Vibration Survival	=4 hours at resonant frequency
Environmental Strength Capability	Double cable weight

Packed Dimensions

Height	15.6 cm 6.1 in
Length	10.8 cm 4.3 in
Shipping Weight	0.42 kg 0.93 lb

SSH-78



Width 14.8 cm | 5.8 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system