

**42396A-5****Butterfly Hanger for 7/8 in coaxial cable and elliptical waveguide 85 and 90**

Dimensions

| | |
|------------------------------|----------------------|
| Nominal Size | 7/8 in |
| Compatible Diameter, maximum | 30.988 mm 1.220 in |
| Compatible Diameter, minimum | 26.670 mm 1.050 in |
| Height | 42.00 mm 1.65 in |
| Length | 63.50 mm 2.50 in |
| Width | 38.10 mm 1.50 in |

Electrical Specifications

| | |
|--------------------|--------|
| DTF Effect | 0.1 dB |
| Return Loss Effect | 0.1 dB |

General Specifications

| | |
|-------------------|---|
| Hanger Type | Standard butterfly hanger |
| Cables per Hanger | 1 |
| Color | Silver |
| Material Type | Stainless steel |
| Ordering Note | CommScope® standard product in Mexico, Central America, and South America CommScope® standard product in the United States and Canada |
| Package Quantity | 10 |

Mechanical Specifications

| | |
|---|--------------------------------------|
| Corrosion Resistance, minimum with no degradation | =500 hours in salt spray chamber |
| Mounting | 3/8 in (M10) drilled cable ladder |
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| Vibration Survival | =4 hours at resonant frequency |
| Environmental Strength Capability | Double cable weight |

Packed Dimensions

| | |
|-----------------|-------------------|
| Height | 25.4 cm 10.0 in |
| Length | 11.4 cm 4.5 in |
| Shipping Weight | 0.49 kg 1.08 lb |
| Width | 9.5 cm 3.7 in |

42396A-5

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

China RoHS SJ/T 11364-2006

ISO 9001:2008

Classification

Compliant

Below Maximum Concentration Value (MCV)

Designed, manufactured and/or distributed under this quality management system

